

**BITUMEN/BUTYL RUBBER GASKET**

<u>PRODUCT</u>	<u>MANUFACTURER</u>
Bidco C-56	Bidco Sealants, Inc. 60 Louise Street Bonne Terre, MO 63628
Conseal CS-102 Conseal CS-102B Conseal CS-202	Concrete Sealants, Inc. P.O. Box 176 New Carlisle, OH 45344
Evergrip 990 ( <u>Only</u> Lots dated on or after 8/31/99)	Martin Asphalt Co. (formerly Gulf States Asphalt Co. ) Three Riverway, Suite 400 Houston, TX 77056
BUTYL-NEK RAM-NEK	Henry Sealant Division 1277 Boyles Street Houston, TX 77020

**Method of Documentation of Acceptance:** By brand and manufacturer.

**Procedure for Approval:** Product samples must be submitted to the Materials Division. Preformed rubber gaskets and bitumen/butyl rubber gaskets must meet the requirements of AASHTO M 198. Tubular cross-section, closed cellular gaskets must meet the physical requirements of ASTM D 1056 (Type 2, Class C, Grade 1) and the chemical requirements of AASHTO M 198. Materials submitted for testing shall be accompanied by a MSDS, actual lot/batch certified analysis, and product literature. This product literature should include, as a minimum, such items as: installation procedures, weather restrictions to use, primer requirements, etc. After approval for inclusion in the Qualified Products List, samples will be taken at random from shipments.

Non-conformance of any material may be cause for the product to be removed from the Qualified Products List.